



Model Calipoint - 34
34 LITRE ALUMINIUM CYLINDER

CSL is an ISO 9001:2015 Certified Company with over 20 years of experience in calibration gas and analytical instrumentation industry, with a state of the art production techniques, equipments and team of highly qualified professionals. Specialized gas handling equipments enables CSL to provide you with a complete solution for all your analytical problems.

Contents 34 Litre

Service Pressure 500 PSI/35 Barg

Dimensions
Diameter 60 mm
Height 250 mm

Weight (kg) 1.2

Standards NPL & NIST traceable
 Manufactured Gravimetrically to ISO 6142

Stability

Non Reactive Gases (LELs/Hydrocarbons)	36 months
Ethanol/ Methanol	12 months
H2S, SO2,NO,Four Gas Mix, NO2	24 months
Cl2 and HCl (min 5 PPM)	9 months

Cylinder Material & Valve
 Aluminium - as per ISO 11118
 Connection C10 Valve (5/8"-18UNF)

Mixture Accuracy
 Minor Components are Certified to the following Tol
 2 - 20 ppm = +/- 10%
 21 - 50 ppm = +/- 5%
 51 - 300ppm = +/- 2%



Equipments

Cylinder valve compatible with all major manufactures regulatros
Fixed flow regulators available at 0.5, 1.0, 2.5 and 3.0 LPM
Variflow regulator (Non - Reactive gases)
Demand Flow Regulators.